

Specifications are subject to change without any prior written notice.

*Control of LEDs depends on the Pixel Flip setting.

DMX CHANNEL MODE										VALUE	FUNCTION	
1CH:04	2CH:04	6CH	1CH:08	2CH:08	10CH	12CH	56CH	58CH	60CH	63CH		16 BIT CHANNELS
	1	1	1	1	1	1						RED LED - All LEDs [1-14]
											0-255	Red (0-Black - 255-100%)
				2								RED LED FINE - All LEDs [1-14]
											0-255	Red (0-Black - 255-100%)
	2	2	2	3	2	2						GREEN LED - All LEDs [1-14]
											0-255	Green (0-Black - 255-100%)
				4								GREEN LED FINE - All LEDs [1-14]
											0-255	Green (0-Black - 255-100%)
	3	3	3	5	3	3						BLUE LED - All LEDs [1-14]
											0-255	Blue (0-Black - 255-100%)
				6								BLUE LED FINE - All LEDs [1-14]
											0-255	Blue (0-Black - 255-100%)
	4	4	4	7	4	4						WHITE LED - All LEDs [1-14]
											0-255	White (0-Black - 255-100%)
				8								WHITE LED FINE - All LEDs [1-14]
											0-255	White (0-Black - 255-100%)
							1	1	1	1		RED LED - LED [1]
											0-255	Red (0-Black - 255-100%)
							2	2	2	2		GREEN LED - LED [1]
											0-255	Green (0-Black - 255-100%)
							3	3	3	3		BLUE LED - LED [1]
											0-255	Blue (0-Black - 255-100%)
							4	4	4	4		WHITE LED - LED [1]
											0-255	White (0-Black - 255-100%)
							5	5	5	5		RED LED - LED [2]
											0-255	Red (0-Black - 255-100%)
							6	6	6	6		GREEN LED - LED [2]
											0-255	Green (0-Black - 255-100%)
							7	7	7	7		BLUE LED - LED [2]
											0-255	Blue (0-Black - 255-100%)
							8	8	8	8		WHITE LED - LED [2]
											0-255	White (0-Black - 255-100%)
							9	9	9	9		RED LED - LED [3]
											0-255	Red (0-Black - 255-100%)
							10	10	10	10		GREEN LED - LED [3]
											0-255	Green (0-Black - 255-100%)
							11	11	11	11		BLUE LED - LED [3]
											0-255	Blue (0-Black - 255-100%)
							12	12	12	12		WHITE LED - LED [3]
											0-255	White (0-Black - 255-100%)
							13	13	13	13		RED LED - LED [4]
											0-255	Red (0-Black - 255-100%)
							14	14	14	14		GREEN LED - LED [4]
											0-255	Green (0-Black - 255-100%)
							15	15	15	15		BLUE LED - LED [4]
											0-255	Blue (0-Black - 255-100%)
							16	16	16	16		WHITE LED - LED [4]
											0-255	White (0-Black - 255-100%)
							17	17	17	17		RED LED - LED [5]
											0-255	Red (0-Black - 255-100%)
							18	18	18	18		GREEN LED - LED [5]
											0-255	Green (0-Black - 255-100%)
							19	19	19	19		BLUE LED - LED [5]
											0-255	Blue (0-Black - 255-100%)
							20	20	20	20		WHITE LED - LED [5]
											0-255	White (0-Black - 255-100%)
							21	21	21	21		RED LED - LED [6]
											0-255	Red (0-Black - 255-100%)
							22	22	22	22		GREEN LED - LED [6]
											0-255	Green (0-Black - 255-100%)
							23	23	23	23		BLUE LED - LED [6]
											0-255	Blue (0-Black - 255-100%)
							24	24	24	24		WHITE LED - LED [6]
											0-255	White (0-Black - 255-100%)
							25	25	25	25		RED LED - LED [7]
											0-255	Red (0-Black - 255-100%)
							26	26	26	26		GREEN LED - LED [7]
											0-255	Green (0-Black - 255-100%)
							27	27	27	27		BLUE LED - LED [7]
											0-255	Blue (0-Black - 255-100%)
							28	28	28	28		WHITE LED - LED [7]
											0-255	White (0-Black - 255-100%)

ELATION® ACL CURTAIN™

DMX Channel Values / Functions Version 1 (63 DMX Channels)

Specifications are subject to change without any prior written notice.

*Control of LEDs depends on the Pixel Flip setting.

DMX CHANNEL MODE											VALUE	FUNCTION
1CH:04	2CH:04	6CH	1CH:08	2CH:08	10CH	12CH	56CH	58CH	60CH	63CH		16 BIT CHANNELS
							29	29	29	29		RED LED - LED [8]
											0-255	Red (0-Black - 255-100%)
							30	30	30	30		GREEN LED - LED [8]
											0-255	Green (0-Black - 255-100%)
							31	31	31	31		BLUE LED - LED [8]
											0-255	Blue (0-Black - 255-100%)
							32	32	32	32		WHITE LED - LED [8]
											0-255	White (0-Black - 255-100%)
							33	33	33	33		RED LED - LED [9]
											0-255	Red (0-Black - 255-100%)
							34	34	34	34		GREEN LED - LED [9]
											0-255	Green (0-Black - 255-100%)
							35	35	35	35		BLUE LED - LED [9]
											0-255	Blue (0-Black - 255-100%)
							36	36	36	36		WHITE LED - LED [9]
											0-255	White (0-Black - 255-100%)
							37	37	37	37		RED LED - LED [10]
											0-255	Red (0-Black - 255-100%)
							38	38	38	38		GREEN LED - LED [10]
											0-255	Green (0-Black - 255-100%)
							39	39	39	39		BLUE LED - LED [10]
											0-255	Blue (0-Black - 255-100%)
							40	40	40	40		WHITE LED - LED [10]
											0-255	White (0-Black - 255-100%)
							41	41	41	41		RED LED - LED [11]
											0-255	Red (0-Black - 255-100%)
							42	42	42	42		GREEN LED - LED [11]
											0-255	Green (0-Black - 255-100%)
							43	43	43	43		BLUE LED - LED [11]
											0-255	Blue (0-Black - 255-100%)
							44	44	44	44		WHITE LED - LED [11]
											0-255	White (0-Black - 255-100%)
							45	45	45	45		RED LED - LED [12]
											0-255	Red (0-Black - 255-100%)
							46	46	46	46		GREEN LED - LED [12]
											0-255	Green (0-Black - 255-100%)
							47	47	47	47		BLUE LED - LED [12]
											0-255	Blue (0-Black - 255-100%)
							48	48	48	48		WHITE LED - LED [12]
											0-255	White (0-Black - 255-100%)
							49	49	49	49		RED LED - LED [13]
											0-255	Red (0-Black - 255-100%)
							50	50	50	50		GREEN LED - LED [13]
											0-255	Green (0-Black - 255-100%)
							51	51	51	51		BLUE LED - LED [13]
											0-255	Blue (0-Black - 255-100%)
							52	52	52	52		WHITE LED - LED [13]
											0-255	White (0-Black - 255-100%)
							53	53	53	53		RED LED - LED [14]
											0-255	Red (0-Black - 255-100%)
							54	54	54	54		GREEN LED - LED [14]
											0-255	Green (0-Black - 255-100%)
							55	55	55	55		BLUE LED - LED [14]
											0-255	Blue (0-Black - 255-100%)
							56	56	56	56		WHITE LED - LED [14]
											0-255	White (0-Black - 255-100%)

ELATION® ACL CURTAIN™												
DMX Channel Values / Functions Version 1 (63 DMX Channels)												
Specifications are subject to change without any prior written notice.												
*Control of LEDs depends on the Pixel Flip setting.												
DMX CHANNEL MODE											VALUE	FUNCTION
1CH:04	2CH:04	6CH	1CH:08	2CH:08	10CH	12CH	56CH	58CH	60CH	63CH		16 BIT CHANNELS
												COLOR MACROS
												0 NO Function
												1-4 Color Macro 01
												5-8 Color Macro 02
												9-12 Color Macro 03
												13-16 Color Macro 04
												17-20 Color Macro 05
												21-24 Color Macro 06
												25-28 Color Macro 07
												29-32 Color Macro 08
												33-36 Color Macro 09
												37-40 Color Macro 10
												41-44 Color Macro 11
												45-48 Color Macro 12
												49-52 Color Macro 13
												53-56 Color Macro 14
												57-60 Color Macro 15
												61-64 Color Macro 16
												65-68 Color Macro 17
												69-72 Color Macro 18
												73-76 Color Macro 19
												77-80 Color Macro 20
												81-84 Color Macro 21
												85-88 Color Macro 22
												89-92 Color Macro 23
												93-96 Color Macro 24
												97-100 Color Macro 25
												101-104 Color Macro 26
												105-108 Color Macro 27
												109-112 Color Macro 28
												113-116 Color Macro 29
												117-120 Color Macro 30
												121-124 Color Macro 31
												125-128 Color Macro 32
												129-132 Color Macro 33
												133-136 Color Macro 34
												137-140 Color Macro 35
												141-144 Color Macro 36
												145-148 Color Macro 37
												149-152 Color Macro 38
												153-156 Color Macro 39
												157-160 Color Macro 40
												161-164 Color Macro 41
												165-168 Color Macro 42
												169-172 Color Macro 43
												173-176 Color Macro 44
												177-180 Color Macro 45
												181-184 Color Macro 46
												185-188 Color Macro 47
												189-192 Color Macro 48
												193-196 Color Macro 49
												197-200 Color Macro 50
												201-204 Color Macro 51
												205-208 Color Macro 52
												209-212 Color Macro 53
												213-216 Color Macro 54
												217-220 Color Macro 55
												221-224 Color Macro 56
												225-228 Color Macro 57
												229-232 Color Macro 58
												233-236 Color Macro 59
												237-240 Color Macro 60
												241-244 Color Macro 61
												245-248 Color Macro 62
												249-252 Color Macro 63
												253-255 Color Macro 64

ELATION® ACL CURTAIN™													
DMX Channel Values / Functions Version 1 (63 DMX Channels)													
Specifications are subject to change without any prior written notice.													
*Control of LEDs depends on the Pixel Flip setting.													
DMX CHANNEL MODE											VALUE	FUNCTION	
1CH:04	2CH:04	6CH	1CH:08	2CH:08	10CH	12CH	56CH	58CH	60CH	63CH		16 BIT CHANNELS	
2			6		5	6				57	57	SHUTTER / STROBE	
												0-31	NO Function
												32-63	LEDs ON
												64-95	Strobe Effect SLOW to FAST
												96-127	LEDs ON
												128-159	Pulse Effect In Sequence SLOW to FAST
												160-191	LEDs ON
												192-223	Random Strobe Effect SLOW to FAST
224-255	LEDs ON												
3		5	7		6	7			57	58	58	MASTER DIMMER	
												0-255	0 to 100%
4		6	8		7	8			58	59	59	DIMMER FINE [16BIT]	
												0-256	1 to 100%
					8	9					60	AUTO PROGRAMS	
												0	NO FUNCTION
												1-20	PROGRAM MACRO 01
												21-40	PROGRAM MACRO 02
												41-60	PROGRAM MACRO 03
												61-80	PROGRAM MACRO 04
												81-100	PROGRAM MACRO 05
												101-120	PROGRAM MACRO 06
												121-140	PROGRAM MACRO 07
												141-160	PROGRAM MACRO 08
												161-180	PROGRAM MACRO 09
												181-200	PROGRAM MACRO 10
												201-220	PROGRAM MACRO 11
												221-240	PROGRAM MACRO 12
												241-260	PROGRAM MACRO 13
251-255	PROGRAM MACRO 14												
					9	10					61	AUTO PROGRAM SPEED	
												0-255	Program Speed SLOW to FAST
					10	11					62	AUTO PROGRAM FADE	
												0-255	Program Fade SLOW to FAST
						12				60	63	DIMMING CURVE MODES	
												0-20	STANDARD
												21-40	STAGE
												41-60	TV
												61-80	ARCHITECTURAL
												81-100	THEATRE
101-255	Default to Unit Setting												

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA, 90040
 323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
 +31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu