

## Technical Specifications - H30 Series

Types	Ladder (L), Triangular (D), Square (V)
Alloy	EN AW 6082 T6
Main Tubes (Chords)	48,3 x 3 mm
Braces	16 x 2 mm
Coupling System	CCS6

## Type H30V

Allowable Normal Force in Main Chord	N	30,54	kN
Allowable Normal Force in Diagonals	N	7,04	kN
Surface area Complete Truss	A	16,96	cm <sup>2</sup>
Moment of Inertia Y-axis	I <sub>y</sub>	2095,9	cm <sup>4</sup>
Moment of Inertia Z-axis	I <sub>z</sub>	2095,9	cm <sup>4</sup>
Allowable bending moment Y-axis	M <sub>y</sub>	14,60	kNm
Allowable bending moment Z-axis	M <sub>z</sub>	14,60	kNm
Allowable shear force Z-axis	Q <sub>z</sub> /V <sub>z</sub>	9,95	kN
Allowable shear force Y-axis	Q <sub>y</sub> /V <sub>y</sub>	9,95	kN
Self-weight	kg	6,3	kg/m

## H30 Series - Standard available Lengths and Codes

Metres	Feet	Code*
0.25/1.00 m in 5 mm steps	0.82'/3.28', in 0.2' steps	
0,25	0.82	H30V-L025
0,29	0.95	H30V-L029
0,50	1.64	H30V-L050
0,71	2.33	H30V-L071
0,75	2.46	H30V-L075
1,00	3.28	H30V-L100
1,50	4.57	H30V-L150
2,00	6.56	H30V-L200
2,50	8.20	H30V-L250
3,00	9.84	H30V-L300
3,50	11.48	H30V-L350
4,00	13.12	H30V-L400
4,50	14.76	H30V-L450
5,00	16.40	H30V-L500