



FEATURES

Innovative IP65 Rated Moving Head Beam Luminaire
Philips™ MSD Platinum14R 280W 80CRI, 7,800K Lamp
Precise 2.5° Beam Aperture and Advanced Optics
Revolutionary Internal Thermal Cooling System
Full CMY Color Mixing

Full CMY Color Mixing

13 Dichroic Colors including CTB, CTO, and UV

8 Rotating Interchangeable and 13 Static-Stamped Gobos

5 and 32 Facet Rotating Prisms and Frost Filter

Motorized Focus and Auto-Focus

High Speed Mechanical Shutter and Strobe

DMX, RDM, Art-NET, and sACN Support

Elation's E-FLY™Internal Wireless DMX Transceiver



The PROTEUS BEAM™ an innovative full featured IP65 rated moving head beam luminaire with the Philips™ MSD Platinum 14R 280W 80CRI 7,800K lamp producing over 12,000 total lumens. Features include an advanced optical system producing a precise 2.5° beam aperture, a revolutionary internal thermal cooling system, full CMY color mixing, 13 dichroic colors including CTB, CTO, and UV, 8 rotating interchangeable and 13 static-stamped metal gobos, 5 and 32 facet rotating prisms, frost filter, motorized focus and auto-focus, high speed mechanical shutter and strobe, DMX, RDM, Art-NET, and sACN protocol support, Elation's E-FLY™ internal wireless DMX transceiver, IP rated 5pin XLR and RJ45 etherCON in/out connections, powerCON TRUE1 in, full color 180° reversible menu display with 6 button touch control panel, battery backup for display power, 500W max power consumption, and a multivoltage universal auto switching power supply (100-240v).



PRODUCT SPECIFICATIONS

SOURCE

Philips MSD Platinum 14R 280W 80CRI 7,800K Lamp 1,500 Hour Average Lamp Life*

*May vary depending on several factors including but not limited to:

Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control and Dimming.

PHOTOMETRIC DATA

80CRI | >12,000 Lumens

136,800 LUX 12,709 FC @49.2' (15m) (2.5° Full ON)

5 and 32 Facet Rotating Prisms and Prism Macros Frost Filter Hybrid Wash Effect Motorized Focus and Auto-Focus High Speed Mechanical Shutter and Strobe

13 Dichroic Colors including CTB, CTO, and UV Full CMY Color Mixing

GOBOS

(8) Interchangeable Rotating / Indexing Glass Gobos (13) Static-Stamped Metal Gobos

CONTROL / CONNECTIONS

(3) DMX Channel Modes (28 total channels) 6 Button Touch Control Panel Full Color 180° Reversible LCD Menu Display 8 / 16 Bit Resolution Adjustable Movement DMX, RDM, Art-NET and sACN Protocol Support Elation E-FLY™ Internal Wireless DMX Transceiver IP65 5pin DMX In/Out IP65 RJ45 Ethernet In/Out IP65 powerCON TRUE1 Power In

SIZE / WEIGHT

Length: 17.1" (445mm) Width: 17.87" (454mm)

Vertical Height: 26.77" (680mm) Weight: 77.0 lbs. (35.0 kg)

ELECTRICAL / THERMAL

AC 100-240V - 50/60Hz 500W Max Power Consumption 14°F to 113°F (-10°C to 45°C)

APPROVALS / RATINGS



IP65



ORDERING INFORMATION PRB014 PROTEUS BEAM™ DRCPROTBEAM Dual Touring Road Case For PROTEUS BEAM™ TRIGGER CLAMP Heavy Duty Wrap Around Hook Style Clamp EFL001 E-FLY™ Wireless DMX Transceiver SCABLE60 24" (610mm) 60 lbs. (27 kg) Rated Safety Cable

PHOTOMETRIC DATA


2.5° Beam Aperture

	15 m	49.2 ft	20 m	65.6 ft	25 m	82.0 ft
Diameter	0.66	2.2	0.88	2.9	1.1	3.6
	lux	fc	lux	fc	lux	fc

COLORS AND GOBOS



INTERCHANGEABLE-ROTATING GOBO WHEEL 1





IMPORTANT NOTICE REGARDING GOBO DIMENSIONS AND CUSTOM GOBOS

Due to the extreme high temp optical system, special material and design requirements are required. Please contact ELATION Customer Support for specific details.

DIMENSIONAL DIAGRAMS

