



Philips Signage Solutions  
Q-Line Display

49"

4K UHD (3840 x 2160)  
Ultra HD

**Signage**Solutions

49BDL3050Q

## Intensify your signage experience

With priceless performance

Deliver startingly clear images in a more eco-friendly way with the Q-Line display. High on performance and reliability, yet low on power consumption, it is ideal for projects where no compromise is accepted.

### **Optimised for public viewing**

- 4K Ultra HD: resolution like you've never seen before

### **Innovative solutions for any signage application**

- Android: Run your own app or choose your favourite app to run
- CMND: Take control of your displays
- Create and update content with CMND & Create
- Schedule what you want, when you want with SmartPlayer
- Connect and control your content via the cloud with HTML5

### **Care about you, your business and your audience**

- Manage settings of multiple displays with CMND & Control
- SmartPower for energy saving

# PHILIPS

# Highlights

## 4K Ultra-HD Resolution

See your Signage Solutions like never before thanks to four times the resolution of a conventional Full HD display. 3840 x 2160 pixels provide an image so refined, so lifelike, it's a window to a new world.

## Powered by Android


With Android OS integrated into the display, you can work with the most developed OS on the planet and save your own app directly into the display. Or, choose from the large library of Android apps and play content from there. With the built-in scheduler, you can daypart your apps and content based on your customer and time of day and with the auto-orientation feature, showing content in portrait or landscape is as simple as turning the display.

## CMND and Control



With CMND & Control, easily manage multiple displays in a central location. With real time display monitoring, setting and software updates from a remote location, and the ability to customise and configure multiple displays at once, such as video wall or menu board displays, controlling your suite of displays has never been easier.

## CMND



A robust display management platform, CMND puts the power back into your hands. Update and manage content with CMND & Create or control your settings with CMND & Control. It's all possible with CMND.

## CMND and Create



Design and create compelling content with CMND & Create, a powerful authoring tool. With a drag and drop interface, preloaded templates, and integrated widgets, you'll be able to amaze your customers with compelling content. Available in portrait and landscape mode.


## SmartBrowser



Connect and control your content via the cloud with the integrated HTML5 browser. Design your signage content online and connect it with a display or with your entire


network. Simply plug in a RJ45 Internet cable for network connection and connect the display with the dedicated URL address, and you are ready to play your cloud-based content.

## SmartPlayer



Turn your USB into a true cost-effective digital signage device. Simply save your content (video, audio, pictures) on your USB and plug into your display. Create your playlist and schedule your content via the on-screen menu, and enjoy your own playlists anytime, anywhere.

## SmartPower



The backlight intensity can be controlled and pre-set by the system to reduce the power consumption by up to 50%, which saves substantially on energy costs.

# Specifications

## Picture/Display

- Diagonal screen size: 48.5 inch / 123.2 cm
- Panel resolution: 3840 x 2160
- Optimum resolution: 3840 x 2160 @ 60 Hz
- Brightness: 350 cd/m<sup>2</sup>
- Contrast ratio (typical): 1200:1
- Response time (typical): 9 ms
- Aspect ratio: 16:9
- Viewing Angle (H / V): 178 / 178 degree
- Pixel pitch: 027963 x 027963 mm
- Display colours: 1.07 Billion
- Picture enhancement: 3/2 - 2/2 motion pull down, 3D Combfilter, Progressive scan, 3D MA deinterlacing, Dynamic contrast enhancement, Colour Enhancement, Colour Temperature Adjustment, De-interlacer, Noise Reduction, Smart Picture
- Operating system: Android 5.1
- Panel technology: IPS

## Supported Display Resolution

### • Computer formats

Resolution	Refresh rate
1280 x 768	60 Hz
1280 x 800	60 Hz
1360 x 768	60 Hz
1280 x 1024	60 Hz
720 x 400	70 Hz
1024 x 768	60, 75 Hz
800 x 600	60, 75 Hz
1600 x 1200	60 Hz
1920 x 1080	60 Hz
640 x 480	60, 72, 75 Hz

### • Video formats

Resolution	Refresh rate
720p	50, 60 Hz
1080p	50, 60 Hz
1080i	25, 30 Hz
480i	30, 60 Hz
576i	25, 50 Hz
480p	30, 60 Hz
576p	25, 50 Hz
2160p	30, 50, 60 Hz

## Connectivity

- Video input: DVI-D, VGA (Analogue D-Sub), USB, HDMI (x 2)
- Audio input: 3.5-mm jack
- Audio output: Audio Left/Right (RCA)

- External control: RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack, RJ45
- Other connections: Analogue (D-sub input), Analogue audio Left/Right out, DVI-D, HDMI in 2x, IR out, micro SD, PC Audio in, PC-In VGA, USB, USB 2.0, VGA in

## Convenience

- Screen-saving functions: Pixel Shift, Low Brightness
- Keyboard control: Lockable
- Network controllable: LAN (RJ45), RS232, RJ45
- Energy-saving functions: Smart Power
- Placement: Landscape
- Remote control signal: Lockable
- Ease of installation: Remote Control Lock
- Memory: 8 GB eMMC
- Other convenience: Kensington lock, VESA mount (400 x 200 mm)
- Signal Loop Through: IR Loop through, RS232
- Tiled Matrix: Up to 10 x 15

## Dimensions

- Bezel width: 11.9 (Top/Left/Right) 14.4 (Bottom) mm
- Set dimensions (W x H x D): 1099.2 x 631.9 x 62.4 mm
- Set dimensions in inch (W x H x D): 43.28 x 24.88 x 2.46 inch
- Product weight: 11.5 kg
- Product weight (lb): 25.36 lb
- VESA Mount: 400 x 400 mm, M6

## Operating conditions

- Altitude: 0 ~ 3000 m
- Temperature range (operation): 0 ~ 40 °C
- Temperature range (storage): -20 ~ 60 °C
- Relative humidity: 20 ~ 80 (operation), 10 - 90% (storage) %
- MTBF: 50,000 hour(s)

## Power

- Mains power: 100 ~ 240 VAC, 50 ~ 60 Hz
- Consumption (On mode): 125 W
- Standby power consumption: <0.5 W
- Power Saving Features: Smart Power

## Sound

- Built-in speakers: 2 x 10 W RMS

## Accessories

- Included accessories: AC Power Cord, RS232 cable, Batteries for remote control, Quick start guide, Remote Control, IR sensor cable (1.8 M)
- Optional accessories: Tabletop stand
- Included Accessories: RS232 daisy-chain cable, USB Cover and screw x 1

## Multimedia Applications

- USB Playback Video: MKV, MP4, MPEG, MPG, TS, VOB, WMV, ASF, AVI, DAT, FLV, WEBM
- USB Playback Picture: BMP, JPEG, JPG, PNG
- USB Playback Audio: AAC, M4A, MP3, WMA


## Miscellaneous

- Warranty: 3-year warranty
- On-Screen Display Languages: Arabic, Simplified Chinese, Traditional Chinese, English, French, German, Italian, Polish, Russian, Spanish, Turkish, Japanese, Czech, Danish, Dutch, Finnish, Norwegian, Portuguese, Swedish
- Regulatory approvals: CE, UL/cUL, CB, FCC, Class B, BSMI, CCC, EAC, EMF, EnergyStar 7.0, PSB

## Internal Player

- Storage: 8 GB eMMC
- CPU: Quad Core Full HD
- Memory: 2 GB DDR3

Philips 49BDL3050Q  
Version 1.0  
Release Date: 10/1/2015



Issue date 2018-03-09

Version: 5.0.2

12 NC: 8670 001 42313  
EAN: 87 12581 74363 5

© 2018 Koninklijke Philips N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips N.V.  
or their respective owners.

[www.philips.com](http://www.philips.com)